



ATF Dexron III

Automatic Transmission & Power Steering Fluid

Product Description

Optilube® ATF Dexron III is a premium multifunctional fully formulated automatic transmission fluid for use in all automatic and powershift transmissions as well as industrial mobile hydraulic systems.

Specifications:

Optilube® ATF Dexron III meets or exceeds the following performance requirements:

- GM Dexron III
- Mercedes-Benz
- Ford Mercon
- Renk
- ZF
- Voith
- Caterpillar TO-2
- Allison C4
- Hydraulic Pump Systems: Sperry-Vickers, Sunstrand and Denison

Features/Benefits:

- Anti-Foam Protection
- Gold Seal Compatibility
- High Chemical and Thermal Stability
- Reduced Harmful Deposits
- Improved Protection for Continuous High Temperature Operation
- Increased Fuel Economy – Reducing Friction Losses
- Low Temperature Fluidity

Properties Physical Typical:

Density, g.ml-3 @ 15°C	0.858
Flash Point, COC	210°C
Viscosity	
Kinematic, 100°C	7.5cSt
Pour Point	-36°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

Premium brand quality without the premium price

For more information please contact: +44 (0)1922 406664 | info@optichemicals.com
www.optichemicals.com