



Universal Automatic Transmission Fluid ATF Dexron II

Product Description

Optilube® ATF Dexron II is a high performance multi-application fluid meeting General Motors 6137-M Dexron II and Allison C3 specifications, and is also suitable for Ford transmissions with a red filler cap. The high viscosity index and low pour point makes this product ideal for use in hydraulic systems, power steering and torque convertors.

Specifications:

Optilube® ATF Dexron II meets or exceeds the following performance requirements:

- GM Dexron II D and GM 6137-M
- Caterpillar TO-2
- Allison C4
- Hydraulic Pump Systems: Voith, Sperry-Vickers, Sunstrand and Denison

Features/Benefits:

- Multi-applications: transmissions, torque convertors, power steering, and general hydraulic systems
- Smooth power transmission in all working conditions
- Excellent fluidity at sub-zero temperatures
- Consistent gear change performance
- High oxidation and thermal stability
- Good friction control

Properties Physical Typical:

Density, g.ml-3 @ 15°C	0.869
Flash Point, COC	210°C
Viscosity	
Kinematic, 40°C	42.5 cSt
Kinematic, 100°C	8.3cSt
Viscosity Index	163
Pour Point	-36°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

Premium brand quality without the premium price

For more information please contact: +44 (0)1922 406664 | info@optichemicals.com

www.optichemicals.com