



## 5W/30 Fully Synthetic

### Product Description

Optilube® 5W/30 Fully Synthetic Motor Oil is a super multi-grade engine oil produced from high quality synthetic base oils incorporating the latest additive technology to produce a super high performance engine oil that delivers excellent performance as well as good fuel economy.

### Specifications:

Optilube® 5w/30 Fully Synthetic meets or exceeds the following performance requirements:

- API: SL/CF
- ACEA: A5/B5
- ILSAC-GF-3
- BMW LL-98
- Ford: WSS-MC2 913A, WSS-MC2 913B

### Features/Benefits:

- Reduced Oil Consumption and Emissions
- Protects against Ring Sticking at High Temperatures
- Long-lasting Dispersant Performance and Corrosion Protection
- Very High Standard of Engine Cleanliness
- Exceptional Long Term Anti-Wear Characteristics
- Excellent High and Low Temperature Performance
- Excellent Fuel Efficiency and Sludge Control for Stop-Go City Motoring

### Properties Physical Typical:

Density, g/cm <sup>3</sup> @ 15°C	0.880
Flash Point, COC	208°C
Viscosity	
Kinematic, 40°C	64 cSt
Kinematic, 100°C	10.8cSt
Viscosity Index	137
Pour Point	-40°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

*Premium brand quality without the premium price*

For more information please contact: +44 (0)1922 406664 | [info@optichemicals.com](mailto:info@optichemicals.com)

[www.optichemicals.com](http://www.optichemicals.com)