



## 5W/30 Semi Synthetic

### Product Description

Optilube® 5W/30 semi-synthetic engine oil is a unique combination of highly refined mineral and synthetic base oils incorporating high performance engine oil additives to deliver a lubricant with exceptional performance and engine protection. The reduced frictional characteristics of this 5W/30 oil provides a balance of enhanced fuel economy with extra power output.

### Specifications:

Optilube® 5w/30 Fully Synthetic meets or exceeds the following performance requirements:

- API: SL/CF
- ACEA: A1/B1
- Ford: WSS-MC2 913A, WSS-MC2 913B

### Features/Benefits:

- Excellent Thermal Stability
- Low Chlorine Formulation, (for safer and easier disposal or recycling)
- Improved Fuel Efficiency
- Suitable for use in Ford Zetec engines
- Improved Engine Cleanliness
- Low Oil Consumption and Low Emissions
- Rapid Circulation on Start-up
- Reduced Pinking and Combustion Chamber Deposits at Extreme Temperatures, (300°C)

### Physical Typical:

TBN, mgKOH.g-1	9
Density, g/cm <sup>3</sup> @ 15.6°C (60°F)	0.861
Flash Point, COC	214°C
Viscosity	
Kinematic, 40°C	58 cSt
Kinematic, 100°C	11 cSt
Viscosity Index	137
Pour Point	-40°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

*Premium brand quality without the premium price*

For more information please contact: +44 (0)1922 406664 | [info@optichemicals.com](mailto:info@optichemicals.com)

[www.optichemicals.com](http://www.optichemicals.com)