



## 5W/30 Fully Synthetic GM

### Product Description

Optilube® Fully Synthetic 5W/30 GM is formulated according to the requirements of GM/Vauxhall/Opel petrol and diesel vehicles operating under extended drain intervals. Formulated from high quality synthetic base oils with additive technology especially designed to ensure high cleanliness and prolonged lubricant life it delivers excellent engine performance with reduced emissions and good fuel economy. Fully Synthetic 5W/30 GM provides optimum engine protection even when operating under extreme hot and cold climate conditions, yet maintains maximum performance throughout.

### Specifications:

Optilube® 5w/30 Fully Synthetic GM meets or exceeds the following performance requirements:

- API: SL/CF
- ACEA: A3/B3, A3/B4
- MB: 229.3
- GM: LL-025-A/B
- BMW: Longlife 01
- Porsche
- VW: 502.00, 505.00

### Features/Benefits:

- Reduced Oil Consumption and Emissions
- Long-Lasting Performance and Corrosion Protection
- Very High Standard of Engine Cleanliness
- Excellent Fuel Efficiency and Sludge Control for Stop-Go City Motoring
- Excellent High and Low Temperature Performance
- Suitable for GM/Vauxhall/Opel Petrol and Diesel vehicles operating under extended drain intervals

### Physical Typical:

Density, g/cm <sup>3</sup> @ 15.6°C (60°F)	0.860
Flash Point, COC	220°C
Viscosity	
Kinematic, 40°C	61 cSt
Kinematic, 100°C	11.7 cSt
Viscosity Index	191
Pour Point	-35°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

*Premium brand quality without the premium price*

For more information please contact: +44 (0)1922 406664 | [info@optichemicals.com](mailto:info@optichemicals.com)

[www.optichemicals.com](http://www.optichemicals.com)