



5W/30 Fully Synthetic C3

Product Description

Optilube® Fully Synthetic 5W/30 C3 engine oil is produced from high quality synthetic base oils and top-tier performance additives.

Specifications:

Optilube® 5w/30 Fully Synthetic C3 meets or exceeds the following performance requirements:

- API: SM/CF
- ACEA: A3/B3, A3/B4, C3
- MB: 229.31, 229.51
- GM: Dexos 2 (formerly GM GEOS)
- BMW: Longlife- 04
- PAS B712290
- VW: 502.00, 505.01

Features/Benefits:

- Provides optimum performance and engine protection at temperature extremes and under high performance conditions.
- Low SAPS technology delivers a high level of engine cleanliness and protection from combustion contamination.
- Blended to ensure fuel efficiency, reduced wear and low emissions.
- Suitable for use in petrol and diesel engines requiring VW specified lubricant performance

Physical Typical:

TBN, mgKOH.g-1	7.5
Density, g/cm ³ @ 15.6°C (60°F)	0.856
Flash Point, COC	220°C
Viscosity	
Kinematic, 40°C	61 cSt
Kinematic, 100°C	11.5 cSt
Viscosity Index	167
Pour Point	-40°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

Premium brand quality without the premium price

For more information please contact: +44 (0)1922 406664 | info@optichemicals.com

www.optichemicals.com