



5W/40 Fully Synthetic PD 505.01

Product Description

Optilube® 5W/40 PD 505.01 Fully Synthetic engine oil is produced from high quality synthetic base oils and high level performance additives, especially formulated for use in VW, Audi, Skoda and Ford vehicles fitted with VW unit injector diesel engines.

Specifications:

Optilube® 5w/40 Fully Synthetic PD 505.01 meets or exceeds the following performance requirements:

- API: SM/CF
- ACEA: A3/B3-04, B4-04, C3-04
- MB: 229.31, 229.51
- GM Dexos 2
- BMW: Longlife- 04
- Ford WSS-MC2 917A
- Porsche
- VW: 505.01

Features/Benefits:

- Provides optimum performance and engine protection at temperature extremes and under high performance conditions.
- Mid-low SAPS technology delivers a high level of engine cleanliness and protection from combustion contamination
- Suitable for use in petrol and diesel engines requiring VW specified 505.01 lubricant performance.
- Blended to ensure fuel efficiency, reduced wear and low emissions.

Physical Typical:

TBN, mgKOH.g-1	9
Density, g/cm ³ @ 15.6°C (60°F)	0.850
Flash Point, COC	226°C
Viscosity	
Kinematic, 40°C	95 cSt
Kinematic, 100°C	14.4 cSt
Viscosity Index	156
Pour Point	-40°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

Premium brand quality without the premium price

For more information please contact: +44 (0)1922 406664 | info@optichemicals.com

www.optichemicals.com