



EP 80W / 90 Gear Oil GL5

Product Description

Optilube® EP 80W / 90 GL5 is a high performance extreme pressure gear oil with high anti-scuff properties, meeting the most severe demands of hypoid final drive gears. Suitable for use in all spiral bevel axles steering gearboxes where API GL5 and MIL-L-2105D performance is required.

Specifications:

Optilube® ATF Dexron III meets or exceeds the following performance requirements:

- API GL5
- MAN 341, 342
- Volvo 97313, 97310
- Fiat W90M
- BLS OL 03
- VW 727
- GM 4655
- Ford M2C9002A
- Mack GO-G
- David Brown ET19
- MIL-L-2105D

Features/Benefits:

- Low Foam
- Non-Corrosive Extreme Pressure Performance
- Low Temperature Fluidity
- High Anti-Scuff Protection
- Excellent Shock Load Performance
- Extends Gear Box and Axle Life

Properties Physical Typical:

Density, g/cm ³ @ 15.5°C (60°F)	0.885
Flash Point, COC	230°C
Viscosity	
Kinematic, 40°C	150cSt
Kinematic, 100°C	14.5 cSt
Viscosity Index	90
Pour Point	-15°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

Premium brand quality without the premium price

For more information please contact: +44 (0)1922 406664 | info@optichemicals.com

www.optichemicals.com