



5W/40 Fully Synthetic

Product Description

Optilube® 5W/40 Fully Synthetic is a super multi-grade engine oil produced from high quality synthetic base oils incorporating the latest additive technology to produce a super high performance engine oil that delivers excellent fuel economy.

Fully Synthetic 5W/40 has been developed to provide outstanding performance in the latest multi-valve technology power units requiring lighter viscosity lubricants that must also deliver good protection, film strength and oxidation stability under more demanding operating conditions

Specifications:

Optilube® 5w/40 Fully Synthetic meets or exceeds the following performance requirements:

- API: SL/CF
- ACEA: A3/B3, B4
- MB: 229.3, MB229.1
- BMW: Longlife
- VW: 501.00 / 502.00 / 505.00

Features/Benefits:

- Reduced Oil Consumption and Emissions
- Protects against Ring Sticking at High Temperatures
- Long-lasting Dispersant Performance and Corrosion Protection
- Very High Standard of Engine Cleanliness
- Exceptional Long Term Anti-Wear Characteristics
- Excellent High and Low Temperature Performance
- Excellent Fuel Efficiency and Sludge Control for Stop-Go City Motoring

Physical Typical:

Density, g/cm ³ @ 15.6°C (60°F)	0.854
Flash Point, COC	208°C
Viscosity	
Kinematic, 40°C	87 cSt
Kinematic, 100°C	14.8 cSt
Viscosity Index	154
Pour Point	-39°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

Premium brand quality without the premium price

For more information please contact: +44 (0)1922 406664 | info@optichemicals.com

www.optichemicals.com