



5W/30 Fully Synthetic FS 913C

Product Description

Optilube®5W/30 FS 913C is a fully-synthetic high performance motor oil that delivers outstanding performance with high fuel economy and is suitable for use in Ford vehicles requiring Ford M2C 913C specified performance levels.

Specifications:

Optilube® 5w/30 FS 913C Fully Synthetic meets or exceeds the following performance requirements:

- API: SL/CF
- ACEA: A1/B1, A5/B5
- Ford: M2C 913C
- Renault RN0700

Features/Benefits:

- Good protection against sludge formation
- Excellent piston deposit control
- Excellent protection against wear throughout the engine

Physical Typical:

| | |
|-----------------------------------|---------|
| TBN, mgKOH.g-1 | 10 |
| Density, g.cm ³ @ 15°C | 0.860 |
| Flash Point, COC | 210°C |
| Viscosity | |
| Kinematic, 40°C | 55 cSt |
| Kinematic, 100°C | 9.5 cSt |
| Viscosity Index | 157 |
| Pour Point | -35°C |

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

Premium brand quality without the premium price

For more information please contact: +44 (0)1922 406664 | info@optichemicals.com

www.optichemicals.com