



15W/40 Semi Synthetic Turbo Diesel

Product Description

Optilube® 15W/40 SS is a specially formulated semi-synthetic engine oil meeting stringent European performance specifications for turbo diesel and naturally aspirated petrol and diesel engines working under normal and arduous conditions.

Specifications:

Optilube® 15w/40 Semi Synthetic meets or exceeds the following performance requirements:

- API: SL/CF
- ACEA: A3, B3, B4
- MB: 227.5, MB229.1
- VW: 500.00 / 505.00

Features/Benefits:

- Low Emissions
- Good Corrosion Protection
- Long-Lasting Dispersant and Anti-Wear Performance
- Improved Fuel Efficiency
- High Levels of Engine Cleanliness
- High Temperature Protection against Ring Sticking
- Excellent High and Low Temperature Performance
- Ensured Oil Performance and Reduced Consumption

Physical Typical:

Total Base Number (TBN)	9 mgKOH/g
Specific Gravity, 15°C	0.854
Flash Point, COC	235°C
Viscosity	
Kinematic, 40°C	112 cSt
Kinematic, 100°C	15.0 cSt
Viscosity Index	157
Pour Point	-30°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

Premium brand quality without the premium price

For more information please contact: +44 (0)1922 406664 | info@optichemicals.com
www.optichemicals.com