



## 5W/30 Fully Synthetic C2

### Product Description

Optilube® 15W/40 SS is a specially formulated, fully-synthetic engine oil produced from high quality synthetic base oils and top-tier performance additives. It is specially formulated for use in Euro IV compliant vehicles fitted with after treatment devices.

### Specifications:

Optilube® 5w/30 Fully Synthetic C5 meets or exceeds the following performance requirements:

- API: SN/CF
- ACEA: A5/B5, C2
- Renault RN0700
- PSA B71 2290

### Features/Benefits:

- Suitable for Euro IV compliant engines using after treatment devices.
- Long-Lasting Dispersant and Anti-Wear Performance
- Improved Fuel Efficiency
- High Levels of Engine Cleanliness
- Mid SAPS technology prevents combustion contamination
- Excellent High and Low Temperature Performance
- Ensured Oil Performance and Reduced Consumption

### Physical Typical:

|                         |               |
|-------------------------|---------------|
| Total Base Number (TBN) | 7.3 mgKOH.g-1 |
| Specific Gravity, 15°C  | 0.855         |
| Flash Point, COC        | 220°C         |
| Viscosity               |               |
| Kinematic, 40°C         | 60 cSt        |
| Kinematic, 100°C        | 10 cSt        |
| Viscosity Index         | 153           |
| Pour Point              | -40°C         |

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

*Premium brand quality without the premium price*

For more information please contact: +44 (0)1922 406664 | [info@optichemicals.com](mailto:info@optichemicals.com)

[www.optichemicals.com](http://www.optichemicals.com)