# OPTILUBE OPTIMUM PROTECTION Technical Data



# **Super Red 2-Stroke Motor Oil**

## **Product Description**

Optilube® 2-Stroke Motor Oil is an advanced 2-stroke oil specifically formulated for use in higher RPM machinery, for example Chainsaws, High-Speed Strimmers, Pumps, Mowers, etc.

Optilube® 2-Stroke Motor Oil has been formulated from the finest quality solvent refined mineral based oils with additive technology designed to deliver optimum performance and is dyed red so that its presence in the petrol mixture is readily apparent.

#### **Specifications:**

Optilube® 2-Stroke Motor Oil meets or exceeds the following performance requirements:

- API: SF/CC
- MIL-L- 2104B

# Features/Benefits:

- Excellent Detergency
- Strong Resistance to Spark Plug Fouling
- Reduced Piston Crown and Exhaust Port Deposits
- Reduced Engine Wear
- Reduced Pre-Ignition
- Outstanding Protection Against Rust

#### **Recommendations:**

Under normal running conditions Optilube® 2-Stroke Motor Oil is suitable for use at ratios as low as 50:1 parts petrol:oil, or can be used at different ratios as recommended by the equipment manufacturer.

## **Properties Physical Typical:**

• • • • • • • • • • • • • • • • • • • •	
Appearance:	Red
Density, g.cm-3 @ 15°C	0.906
Flash Point, COC	200°C
Viscosity	
Kinematic, 40°C	120 cSt
Kinematic, 100°C	15.0 cSt
Viscosity Index	98
Pour Point:	-20°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.