



## 75W / 90 Semi Synthetic Gear Oil GL5

### Product Description

Optilube®75W/90 semi-synthetic gear oil is designed to combat problems associated with gear selection and overheating in highly stressed powertrains. Formulated with high technology base stocks and performance additives to provide outstanding lubrication at extreme operating temperatures where conventional oils begin to degrade.

### Specifications:

Optilube® 75W/90 synthetic gear oil meets or exceeds the following performance requirements:

- API: GL5
- MIL: 2105D
- Ford: M2C-175A

### Features/Benefits:

- Excellent Thermal Stability and Resistance to Oxidation
- Fully Compatible with Conventional Gear Oils
- Excellent Rust and Corrosion Protection
- Excellent Anti-Wear and Extreme Pressure Performance
- Excellent Load Stress Capacity

### Properties Physical Typical:

Density, g.ml-3 @ 15.5°C	0.875
Flash Point, COC	190°C
Viscosity	
Kinematic, 40°C	106cSt
Kinematic, 100°C	12.2cSt
Viscosity Index	105
Pour Point	-45°C

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

*Premium brand quality without the premium price*

For more information please contact: +44 (0)1922 406664 | [info@optichemicals.com](mailto:info@optichemicals.com)

[www.optichemicals.com](http://www.optichemicals.com)