



2-Stroke Motor Oil

Product Description

Optilube® 2-Stroke Motor Oil is a traditional mineral oil based motor oil suitable for use in air and water cooled 2-stroke cycle engines typically used in motorcycles, scooters, mopeds, lawnmowers and horticultural equipment.

Optilube® 2-Stroke Motor Oil has been formulated from the finest quality solvent refined mineral based oils with additive technology designed to deliver optimum performance and is dyed blue so that its presence in the petrol mixture is readily apparent.

Specifications:

Optilube® 2-Stroke Motor Oil meets or exceeds the following performance requirements:

- API: SF/CC
- MIL-L- 2104B

Features/Benefits:

- Resistance to High Sulphur Fuels
- Dispersant / Detergent Properties
- Excellent Anti-Wear, Oxidation Stability and Corrosion Protection
- Good Anti-Sludge and Varnish Resistance
- Good Deposit Control

Recommendations:

Under normal running conditions Optilube® 2-Stroke Motor Oil is recommended for use at between 16:1 to 24:1 parts petrol:oil, or as otherwise recommended by the engine manufacturer.

Properties Physical Typical:

Density, g.cm-3 @ 15°C	0.890
Flash Point, COC	240°C
Viscosity	
Kinematic, 40°C	74cSt
Kinematic, 100°C	10.3cSt
Viscosity Index	98

These characteristics are typical of current production material, whilst further production will meet these specifications, some variation may occur.

Premium brand quality without the premium price

For more information please contact: +44 (0)1922 406664 | info@optichemicals.com
www.optichemicals.com